

### 5.6" DIGITAL WIRELESS COLOR REVERSE CAMERA KIT

PART No. **Bi5.6MONWi**

- 10 - 32V Input Voltage Range
- LCD colour monitor with wide viewing angle and high resolution display
- Effective signal distance: 120 m (barrier-free)
- Picture image adjustable for Horizontal, Mirror and Normal viewing
- Frequency range: 2400~2483MHZ
- Automatic backlighting for buttons
- Full-function remote control
- Up to 4 AV inputs. 1 video output and 1 audio output
- Auto switches to image from back-up, left or right-side camera
- On-board speaker
- Waterproof rate (Camera) IP 67



**DIGITAL WIRELESS SYSTEM**

**120M RANGE**

### 4 PIN DOME CAMERA WITH NIGHT VISION

PART No. **BiHDCAM-DOME**



**420 TV LINES**

**92° LENS ANGLE**

- Sharp CCD chip
- Effective Pixels: 512 x 582 pixels
- Resolution: 420 TV Lines
- Minimum Illumination: 1 Lux / F2.0
- Waterproof rate: IP 67

### SMALL CCD CAMERA BUTTERFLY MOUNT

PART No. **BiBUTCAM**



**420 TV LINES**

**92° LENS ANGLE**

- Sharp CCD chip
- Effective Pixels: 512 x 582 pixels
- Resolution: 420 TV Lines
- Dimensions: 30 x 33 x 42mm
- Minimum Illumination: 0 Lux/F1.2
- Waterproof rate: IP 67

### CCD SIDE VIEW REVERSE CAMERA

PART No. **BiSiDECAM**

"Eliminate blind spots entirely with this advanced side view reversing camera."



**420 TV LINES**

**180° LENS ANGLE**

- Sharp CCD chip
- Effective Pixels: 512 x 582 pixels
- Resolution: 420 TV Lines
- Minimum Illumination: 0 Lux/F1.2
- Waterproof rate: IP 67

### 4 PIN CONNECTOR CABLES

- 1 METRE BiLEAD-1**
- 3 METRE BiLEAD-3**
- 7.5 METRE BiLEAD-7.5**
- 10 METRE BiLEAD-10**
- 15 METRE BiLEAD-15**
- 20 METRE BiLEAD-20**



**6mm EXTRA HEAVY DUTY CABLES**

- TRAILER CONNECTOR KIT - 1 INPUT BiLEAD-CT**
- TRAILER CONNECTOR KIT - 2 INPUTS BiLEAD-CT-2**



## REVERSE CAMERA SYSTEMS

### HEAVY DUTY 7" LCD COLOUR MONITOR

PART No. **RKS7MON**



### HEAVY DUTY 5.6" LCD COLOUR MONITOR

PART No. **Bi5HDMON**



HEAVY DUTY

MULTI INPUT COLOUR MONITORS

- 12-48V Input Voltage Range
- 3 Camera Inputs
- High Resolution Digital Screen
- Full-function remote control
- Soft Touch Front Panel Buttons
- Heavy Duty Construction, including Stainless Steel Bracket
- Multiple Video Formats
- Built-in speaker
- 12 Months Commercial Warranty
- Dimensions: 186(L) x 29(D) x 128(H)

**12-48V MULTIVOLT**

**3 CAMERA INPUTS**

- 10-32V Input Voltage Range
- 3 Camera Inputs
- Full-function remote control
- Auto activates on reverse signal
- Mirror, normal, up/down and left/right image switch available
- Built-in speaker
- Automatic brightness control function
- Dimensions: 145 x 136 x 31.5mm

**12-32V MULTIVOLT**

**3 CAMERA INPUTS**



1300 914 868

6 Jarrah Drive Braeside VIC 3195  
sales@rkssales.com.au



6326 1813

5/190 Invermay Rd, Invermay 7248  
rkstas@rkssales.com.au



## 7" LCD COLOUR QUAD MONITOR

PART No. **Bi7HDMON-Q4**



QUAD SPLIT MONITORS

- 10-32V Input Voltage Range
- Built-in quad display splitter
- Single, dual, triple, quad, trefoil, Y-split, PIP1 / PIP2/PIP3/H SPLIT/trefoil image available
- 1 DVD/AV input and 4 camera inputs
- Auto scanning and timed image switch.
- Built-in stereo speaker
- Backup distance grid & left/right-turning indicator arrow available
- Full-function remote control

10-32V MULTIVOLT

4 CAMERA INPUTS



## 9" LCD COLOUR QUAD MONITOR

PART No. **Bi9HDMON-Q4**



- 12-24V Input Voltage Range
- Built-in quad display splitter
- High resolution panel
- PAL & NTSC auto switching
- Built-in stereo speaker
- Auto activates on reverse signal
- Auto scanning and timed image switch
- Backup distance grid & left/right turning indicator arrow available
- Full function remote control

12-24V MULTIVOLT

4 CAMERA INPUTS



## 5" LCD COLOUR MONITOR

PART No. **BSMON1-5**



VALUE Option

- 12-32V Input Voltage Range
- 2 Camera Inputs
- Resolution: 640 x 480
- TV System: PAL/NTSC
- Separate trigger control wire on each input
- Can be mounted on dash top or windscreen
- Full function remote control

12-32V MULTIVOLT

PAL/NTSC CAPABLE

2 CAMERA INPUTS



## 7" LCD COLOUR MIRROR MONITOR

PART No. **BiNP70-NOC**



- 12V Input Voltage Range
- 7" TFT LCD monitor
- 2 Camera Inputs
- TV System: PAL/NTSC
- Clips on to the original mirror bracket
- Built-in touch screen operation
- Dimensions: 259 x 106 x 30mm
- Full function remote control

12V INPUT

PAL/NTSC CAPABLE

2 CAMERA INPUTS



## RKS PREMIUM CCD TRUCK CAMERA WITH NIGHT VISION

PART No. **RKSCAM3**

"Our most popular rear vision camera now significantly upgraded."



SONY HI-RES CCD Chip

Also Available in: **RKSCAM3-120** - 120° viewing angle

- Sony CCD chip
- Resolution: 650 TV Lines
- 92 Degrees viewing angle
- 316 stainless steel bracket
- Mirror and unmirror switchable
- Audio output
- Infrared for superior night vision
- Compatible with all RKS colour monitors
- TV system: NTSC
- Waterproof rate: IP 69K

650 TV LINES

92° LENS ANGLE

IP69K HOUSING



## CCD BULLET CAMERA WITH NIGHT VISION

PART No. **BiHDCCD-LV**



- Sony CCD chip
- Wide angle (120°)
- Infrared LED light: 10 PCS
- IR Distance: 15 m
- Minimum Illumination: 0 Lux
- TV system: NTSC
- Waterproof rate: IP 67

420 TV LINES

120° LENS ANGLE



## CCD REVERSE CAMERA WITH NIGHT VISION

PART No. **BiSMCAM**



- Sharp CCD chip
- Effective Pixels: 512 x 582 pixels
- Resolution: 420 TV Lines
- Minimum Illumination: 0 Lux / F1.2 with IR
- Lens Angle: 180°
- TV system: NTSC

420 TV LINES

180° LENS ANGLE



## CCD LICENCE PLATE CAMERA WITH NIGHT VISION

PART No. **BiLiCCAM-CCD**

"Durable, rustproof steel bodied License Plate Mount Camera."



- Sharp CCD chip
- IR Distance: 3m - 5m
- Dimensions: 198mm x 28mm
- Effective Pixels: 510 x 496 pixels
- Resolution: 420 TV Lines
- Minimum Illumination: 0 Lux / F1.2 with IR
- Lens Angle: 135°
- TV System: NTSC
- Waterproof rate: IP 67

420 TV LINES

135° LENS ANGLE

